

Simple Demapping Methods for Turbo Coded Noncoherent MFSK Systems Under Rayleigh Fading Channels

Min Sagong* *Regular Member*, Kyungwhoon Cheun* *Lifelong Member*

ABSTRACT

This paper proposes new suboptimum, yet very efficient demapping methods for Turbo coded noncoherent MFSK systems under AWGN and Rayleigh fading channels with channel state information. Simulation results show that the proposed methods achieve performance within 0.2 dB of the maximum-likelihood decoder and the previously proposed suboptimum demapping schemes with a fraction of the complexity.

Key Words : Demapping, Frequency Shift Keying, Turbo Codes

I. Introduction

Many communication channels are characterized by a rapid time-varying phase response with AWGN. Under such conditions, accurate phase estimation could be difficult if not impossible. To avoid problems involving accurate phase estimation, noncoherent demodulation schemes such as MFSK may be employed^[1-4].

On the other hand, Turbo codes have been shown to offer impressive performance on the AWGN and fully-interleaved Rayleigh fading channels with coherent modulation schemes such as quadrature amplitude modulation^{[5], [6]}. Optimum demapping of Turbo codes with noncoherent MFSK under AWGN or Rayleigh fading channels with channel state information (CSI) requires the computation of the zeroth order modified Bessel functions of the first kind in computing the channel log-likelihood ratios (LLR)^{[7]-[9]}. Here, CSI refers to the channel amplitude response. In order to bypass the direct evaluation of the complex Bessel functions, Hall and Wilson in [7] proposed an approximation to the exact channel LLR. This approximation shows

negligible performance loss but still requires significant complexity requiring the evaluation of exponential functions. In [8], Valenti and Cheng, additionally proposed applying the Jacobian approximation^[10] to further reduce the decoder complexity.

In this paper, we propose very simple, yet efficient channel LLR approximations under AWGN and Rayleigh fading channels with CSI for Turbo coded noncoherent MFSK systems. The proposed approximations offer performance within 0.2 dB of the maximum-likelihood (ML) decoder and the previously proposed suboptimum demapping schemes with a fraction of the complexity.

The remainder of the paper is organized as follows. In Section II, we introduce the system model and in Section III, we briefly overview the optimum ML decoder and previously proposed suboptimum demapping schemes and propose new channel LLR approximations. In Section IV, simulation results are presented, demonstrating the effectiveness of the proposed methods. Finally, conclusions are drawn in Section V.

* This research was supported by the Ministry of Knowledge Economy, Korea, under the ITRC (Information Technology Research Center) support program supervised by the IITA (Institute of Information Technology Advancement)(IITA-2009-C1090-0902-0037).

* CSC lab, department of electronic and electrical engineering, POSTECH (min40@postech.ac.kr, cheun@postech.ac.kr)
논문번호 : KICS2010-07-299, 접수일자 : 2010년 7월 10일, 최종논문접수일자 : 2010년 8월 5일

II. System Model

The discrete-time model for the system under consideration is shown in Fig. 1. A binary message vector \mathbf{u} of length K is encoded by a binary Turbo encoder to produce a codeword vector \mathbf{b} of length N , assumed to be an integer multiple of $\log_2 M$. The codeword vector is then passed onto the channel interleaver resulting in an interleaved codeword vector $\tilde{\mathbf{b}}$ which is then modulated using an MFSK modulator. The output of the MFSK modulator is represented by an $M \times L$ matrix $\mathbf{S} \equiv [\mathbf{s}_0 \mathbf{s}_1 \cdots \mathbf{s}_{L-1}]$ consisting of $L \equiv N/\log_2 M$ MFSK modulated symbols where \mathbf{s}_i is one of the M possible M -dimensional elementary column vectors. The MFSK modulated signal is then transmitted through a frequency nonselective Rayleigh fading channel represented by a complex fading coefficient vector $\mathbf{c} \equiv [c_0 c_1 \cdots c_{L-1}]$. The i th fading coefficient c_i is given by $c_i = a_i \exp(j\theta_i)$ where a_i and θ_i are the real-valued amplitude and phase responses of the channel corresponding to \mathbf{s}_i . Here, we focus on the AWGN and the independent (fully interleaved) Rayleigh fading channel. For the AWGN channel $a_i = 1$, $i = 0, 1, \dots, L-1$ and the θ_i are independent and identically distributed (i.i.d.) RVs uniformly distributed on $[0, 2\pi)$. For the Rayleigh fading channel, the c_i are i.i.d. zero-mean complex Gaussian RVs with a variance of $1/2$ in each dimension.

Let $\mathbf{y}_i^T \equiv [y_i^0, y_i^1, \dots, y_i^{M-1}]$ where y_i^l denotes the l th matched filter output corresponding to the symbol




Fig. 1. Discrete-time system model of the Turbo coded noncoherent MFSK system

\mathbf{s}_i . Then, the matrix of the receiver matched filter outputs for the code frame can be represented by $\mathbf{Y} \equiv [\mathbf{y}_0 \mathbf{y}_1 \cdots \mathbf{y}_{L-1}]$ where $\mathbf{y}_i = c_i \mathbf{s}_i + \mathbf{n}_i$. The noise vector \mathbf{n}_i is the i th column of an $M \times L$ noise matrix \mathbf{N} whose entries consist of uncorrelated zero-mean complex Gaussian RVs with variance $\sigma^2 = 1/(2\gamma)$ in each dimension where $\gamma \equiv \overline{E_s}/N_0$. Here, $\overline{E_s}$ is the average received energy per MFSK modulated signal and $N_0/2$ is the two-sided noise spectral density of the background thermal noise. Based on each \mathbf{y}_i , the receiver computes the channel LLRs of the $\log_2 M$, interleaved binary code symbols contained in each \mathbf{y}_i . The LLRs of the interleaved binary code symbols, $\tilde{\mathbf{z}} = [\tilde{z}_0 \tilde{z}_1 \cdots \tilde{z}_{N-1}]$ are then deinterleaved to yield $\mathbf{z} = [z_0 z_1 \cdots z_{N-1}]$, containing the channel LLR values of the code frame which is passed onto the iterative Turbo decoder to finally produce the estimated binary message vector $\hat{\mathbf{u}}^{[11]}$.

III. Proposed Channel LLR Approximations

In this section, we propose very simple, yet efficient suboptimum approximations to the channel LLR values required by the iterative Turbo decoder. First, we briefly overview the exact channel LLR and previously proposed approximations. Since the demodulator operates on a symbol-by-symbol basis, we may drop the subscripts of \mathbf{y} and a without ambiguity.

Under the Rayleigh fading channel with CSI, the exact channel LLR for the k th bit contained in an MFSK symbol is given as follows^[9]:

$$z_k \approx \frac{\sum_{l \in A_0^k} I_0(2a\gamma|y^l|)}{\sum_{l \in A_1^k} I_0(2a\gamma|y^l|)} \quad (1)$$

where $k = 0, 1, \dots, \log_2 M - 1$, A_d^k is the set of MFSK symbols whose corresponding k th bit is

$d \in 0,1$ and $I(\cdot)$ is the zeroth order modified Bessel function of the first kind[12]. The channel LLR for the AWGN channel is also given by (1) with $a = 1$. As can be seen from (1), computing the exact channel LLRs for the AWGN and the Rayleigh fading channels with CSI is quite complex, requiring the evaluation of modified Bessel functions. Hall and Wilson in [7] utilized the following approximation in order to bypass direct evaluation of the modified Bessel function:

$$I_0(x) \approx \begin{cases} 1 + 0.25x^2, & \text{if } 0 \leq x \leq 1.8272 \\ e^x / \sqrt{2\pi x}, & \text{otherwise} \end{cases} \quad (2)$$

However, this approximation is still quite complex due to the exponential, square-root and division operations. On the other hand, Valenti and Cheng in [8] employed the Jacobian (Max-Log) approximation[10] to (1) resulting in

$$\tilde{z}_k \approx \max_{l \in A_0^k} (\ln I_0(2a\gamma|y_l|)) - \max_{l \in A_1^k} (\ln I_0(2a\gamma|y_l|)) \quad (3)$$

However, this still does not solve the problem of having to evaluate the modified Bessel function. Valenti and Cheng in [9] proposed using (2) or employing a lookup table for the evaluation of the function $\ln(I_0(x))$.

Fig. 2 shows a plot of the function $y = \ln(I_0(x))$. Notice that for sufficiently large values of x , the function, $y = \ln(I_0(x))$ may be well approximated simply by $y = x$. Hence, applying $\ln(I_0(x)) \approx x$ to (3), we have,

$$\tilde{z}_k \approx 2a\gamma(\max_{l \in A_0^k} (|y_l|) - \max_{l \in A_1^k} (|y_l|)). \quad (4)$$

On the other hand, for small values of x , i.e., low SNR, $\ln(I_0(x))$ can be well approximated by $x^2/4$ [13]. Applying the approximation $\ln(I_0(x)) \approx x^2/4$ to (3), we have,

$$\tilde{z}_k \approx a^2\gamma^2(\max_{l \in A_0^k} (|y_l|^2) - \max_{l \in A_1^k} (|y_l|^2)) \quad (5)$$




Fig. 2. The proposed linear fitting for $\ln(I_0(x))$.

Here, approximation (4) provides a high SNR approximation while (5) provides a low SNR approximation to (3). Note that the computational complexities of the approximations (4) and (5) are clearly orders of magnitude lower compared to (1) or the approximations suggested in [7] and [9]. Since the complexity of calculating the norm squared value of a complex value is smaller than the complexity of calculating its norm, (5) is somewhat simpler than (4). However, simple but accurate approximations for computing the norm of a complex number are widely available in the literature^[14-16]. In the following section, we show that the application of these approximations to (4) results in negligible performance degradations.

IV. Simulation results

In this section, we present the simulation results for the frame error rate (FER) performance for the proposed approximations under the AWGN and the Rayleigh fading channel with CSI. Simulations were performed using the Turbo code as defined in the third-generation partnership project (3GPP) standard^[17] with Max-Log-MAP^[18] decoding. A scaling factor of 0.7 was used for the extrinsic information values exchanged between the constituent decoders^[19]. In all simulations, a frame length of $K = 144$ bits, a code rate of $r = 1/3$ and uniform channel interleaver is assumed. The *linear* and the *square* approximations denote the

approximations based on (4) and (5), respectively.

The FER curves versus \bar{E}_b/N_0 ($\bar{E}_b = \bar{E}_s/r/\log_2 M$) under AWGN and Rayleigh fading channels with CSI are shown in Figs. 3-4. The approximations of Hall and Wilson^[7] and Valenti and Cheng^[9] show performance indistinguishable from that of the exact channel LLR under both channels. We observe that maximum performance losses for the *linear* and the *square* approximations are within 0.1 dB under the AWGN channel. Under the Rayleigh fading channel, the

maximum losses for the two proposed approximations are within 0.2 dB. Note that for high SNRs, the *linear* approximation performs better than the *square* approximation and vice versa for low SNRs, as expected. An appropriate selection of either the *linear* or the *square* approximation depending on the modulation order M guarantees performance losses within 0.1 dB at extremely low complexity.

The FER curves for the *linear* approximation of (4) are also shown in Figs 3 - 4 when the following approximation suggested in [16] is applied to computing $|y^l|$, i.e.,

$$|y^l| \approx \alpha \max(y_{re}^l, y_{im}^l) + \beta \min(y_{re}^l, y_{im}^l). \quad (6)$$

Here, α and β are positive real values chosen so that the mean-squared error is minimized and $y_{re}^l = |Re(y^l)|$ and $y_{im}^l = |Im(y^l)|$. When y^l are zero-mean i.i.d., complex Gaussian RVs, it is easily found that $\alpha = 0.96$ and $\beta = 0.42$. The following simpler approximation to y^l is also given in [15]

$$|y^l| \approx \max(y_{re}^l, y_{im}^l) + 0.5 \min(y_{re}^l, y_{im}^l). \quad (7)$$

Notice that both approximations (6) and (7) for y^l do not incur noticeable degradation in performance. Though not shown, we have also verified that simulation results obtained for other decoding scheme (Log-MAP^[18]), modulation orders, frame lengths and code rates all indicate similar conclusions.

V. Conclusion

New suboptimum, yet very efficient demapping methods for Turbo coded noncoherent MFSK systems under AWGN and Rayleigh fading channels with CSI were proposed. Simulation results indicate that, with a fraction of the complexity, the proposed demapping methods achieve performance within 0.2 dB of the ML decoder and the previously proposed suboptimum demapping schemes.




Fig. 3. FER versus \bar{E}_b/N_0 for various demapping methods under the AWGN channel. Turbo code, Max-log-MAP decoding, scaling factor=0.7, $K=144$ bits, $r=1/3$.




Fig. 4. FER versus \bar{E}_b/N_0 for various demapping methods under the Rayleigh fading channel. Turbo code, Max-log-MAP decoding, scaling factor=0.7, $K=144$ bits, $r=1/3$.

References

- [1] D. Raphaeli, "Noncoherent coded modulation," *IEEE Trans. Commun.*, Vol.44, pp. 172-183, Feb. 1996.
- [2] 전광자, 홍성주, 김영권, "MFSK 변조 방식을 이용한 주파수 도약 대역확산에 관한 연구," *대한전자공학회 학술대회 논문집*, Vol.13, No.1, pp.3-6, Jul. 1990.
- [3] 윤유창, 송홍엽, "연관성 리미터와 결합된 FH / MFSK 시스템의 다중사용자 검출 방법," *한국통신학회논문지*, Vol.27, No.4B, pp.324-330, Apr. 2002.
- [4] 이동현, 손종원, 김용로, 유홍균, "레이리 페이딩 채널환경에서 재머 상태 정보를 이용한 복합재머에 대한 FH/MFSK의 성능 분석," *한국통신학회논문지*, Vol.26, No.8, pp.1183-1188, Aug. 2001.
- [5] C. Berrou, A. Glavieux and P. Thitimajshima, "Near Shannon limit error-correcting coding and decoding: Turbo codes," in *Proc. IEEE ICC'93*, 1993, pp.1064-1070.
- [6] E. K. Hall and S. G. Wilson, "Design and analysis of Turbo codes on Rayleigh fading channels," *IEEE J. Sel. Areas Commun.*, Vol.16, No.2, pp.160-174, Feb. 1998.
- [7] E. K. Hall and S. G. Wilson, "Turbo codes for noncoherent channels," in *Proc. IEEE GLOBECOM, Commun. Theory Mini-Conf.*, Phoenix, AZ, Nov. 1997, pp.66-70.
- [8] A. Ramesh, A. Chockalingam and L. B. Milstein, "Performance of noncoherent Turbo detection on Rayleigh fading channels," in *Proc. IEEE GLOBECOM*, Nov. 2001, pp. 1193-1198.
- [9] M. C. Valenti and S. Cheng, "Iterative demodulation and decoding of Turbo-coded M-ary noncoherent orthogonal modulation," *IEEE J. Sel. Areas Commun.*, Vol.23, No.9, Sept. 2005.
- [10] J. A. Erfanian, S. Pasupathy and G. Gulot, "Reduced complexity symbol detectors with parallel structures for ISI channels," *IEEE Trans. Commun.*, Vol.42, pp.1661-1667, Feb. / Mar. / Apr. 1994.
- [11] C. Caire, G. Taricco and E. Biglieri, "Bit-interleaved coded modulation," *IEEE Trans. Inf. Theory*, Vol.44, No.3, pp.927-946, May 1998.
- [12] M. Abramowitz and I. A. Stegun, *Handbook of mathematical functions with formulas, graphs and mathematical tables*, Dover Publications, inc., New York 1965.
- [13] C. Durand, J. Boutros and E. Villebrun, "Forward error correction of FSK alphabets for noncoherent transmissions over AWGN channel," *IEEE Commun. Lett.*, Vol.4, No. 10, pp.318-320, Oct. 2000.
- [14] M. Barni, V. Cappellini and A. Mecocci, "Fast vector median filter based on Euclidean norm approximation," *IEEE Signal Process. Lett.*, Vol.1, No.6, pp.92-94, June 1994.
- [15] A. E. Filip, "A baker's dozen magnitude approximations and their detection statistics," *IEEE Trans. Aerosp. Electron. Syst.*, Vol.12, pp.86-89, Jan. 1976.
- [16] C. Seol and K. Cheun, "A low complexity Euclidean norm approximation," *IEEE Trans. Signal Process.*, Vol.56, No.4, pp.1721-1726, Apr. 2008.
- [17] The third generation partnership project; Technical specification group radio access network; Multiplexing and channel coding, 1999.
- [18] P. Robertson, E. Villebrun and P. Hoeher, "A comparison of optimal and sub-optimal decoding algorithms in the Log domain," in *Proc. ICC*, pp.1009-1013, June 1995.
- [19] J. Vogt and A. Finger, "Improving the Max-Log-MAP Turbo decoder," *IEEE Electronics Lett.*, Vol.36, No.23, pp.1937-1939, Nov. 2000.

Min Sagong

Regular Member



Min Sagong was born in Taegu, Korea, on July 5, 1979. He received the B.S. degree in electronic and electrical engineering from Pohang University of Science and Technology (POSTECH), Pohang, Korea, in 2005. He is currently working toward the Ph. D. degree in electronic and electrical engineering at POSTECH. His current research interests include OFDMA network and Turbo codes.

Kyungwhoon Cheun

Lifelong Member



Kyungwhoon Cheun was born in Seoul, Korea, on December 16, 1962. He received the B.A. degree in electronics engineering from Seoul National University, Seoul, Korea, in 1985, and the M.S. and Ph.D. degrees from the University of Michigan, Ann Arbor, in 1987 and 1989, respectively, both in electrical engineering. From 1987 to 1989, he was a Research Assistant at the EECS Department at the University of Michigan, and from 1989 to 1991, he joined the Electrical Engineering Department at the University of Delaware, Newark, as an Assistant Professor. In 1991, he joined the Division of Electrical and Computer Engineering at the Pohang University of Science and Technology (POSTECH), Pohang, Korea, where he is currently a Professor. He also served as an engineering consultant to various industries in the area of mobile communications and modem design. His current research interests include turbo codes, RA codes, space-time codes, MIMO systems, UWB communications, cellular and packet radio networks, and OFDM systems.